

FLOORS



DISSIPATIVE FLOOR COATING

It gives dissipative characteristics to a standard floor, and it is excellent in maintaining the conductive floor in operating rooms, clean rooms and data processing centres. It may also be used to maintain the table mat's dissipative surfaces.

First treatment:

- well wash the floor with the **stripper** -rinse with clean water.
- when dry apply two thin coats on the floor. (Yield: 1lt. for approx. 25m² per 2 coats)

Ordinary Maintenance:

- sweep the floor with a wet broom, then wash it with the **cleaner** diluted in water at 1-5% ratio.

Maintenance with spray:

- Dilute the coat in water at 30% ratio, spray it on the floor and then polish by a one-brush machine, provided with a suitable scotch-bride. (Yield: 1lt. for approx. 100m²) Rs: < 10¹¹ Ω

7805.876

LIQUID COAT, 5 Kilos unit



DETERGENT

Low foaming-agent detergent with highly concentrated active substances and alkalinity. It is used for cleaning and maintenance of the waxed surface.

- Biodegradable: up to over 90%
 - Dilution in water: 1-5%
- It may be used to wash by hand and with a one-brush polisher or a washing-drying machine.

7805.873

DETERGENT, 5 Kilos unit

STRIPPER

Dewaxing alkaline detergent have to be used the first time, before applying the coating on the floor. It removes quickly multiple coats of wax and embedded dirt. It is suitable on PVC, Rubber and Hard floors.

- Biodegradable: up to over 90%
 - Dilution in water: 5-10% machine stripping, 12-16% manual stripping
- Lay off the solution and let it act for 5 minutes, then wash with water.

7805.870

FLOOR STRIPPER, 5 Kilos unit

ELECSTAT-C Static Dissipative Agent

ELECSTAT-C is a non-toxic, low foaming, static dissipative agent for cleaning, used to enhance the features of the existing ESD floors or make a non-ESD floor static dissipative.

Rs: < 10¹¹ Ω

Biodegradability: over 90%

Dilution in water: 1 to 2%:

Application: for manual or mechanical cleaning.

7805.885

Dissipative agent ELECSTAT 5kg plastic can



DISSIPATIVE FLOOR PAINT

Two type of paints (Electroguard 30 and Electroguard 40) both in medium gray near to RAL 7035, with an attractive satin gloss finish.

They can be simply applied to existing concrete floors without the need for specialist flooring contractors. They are normally applied with two coats by brush or roller.

7805.853 ELECTROGUARD 30, TWO-PACK water based, static dissipative epoxy paint 5 litre unit (4 litre base, 1 litre activator)
Number of coats: 2 Yield: approx. 8m²/litre Rs 109 – Rg 109

7805.854 ELECTROGUARD 40, SINGLE PACK water based static dissipative acrylic paint, 5 litre unit
Number of coats: 2 Yield: approx. 10m²/litre Rs 109 – Rg 109

7805.856 FLOORPOX EPOXY PRIMER for bare concrete floor
12 litre unit (6 litres base + 6 litres activator)
Number of coats : 2 Yield: approx. 16m²/litre



FLOOR MARKING TAPE

7807.172 PVC adhesive tape, ESD Protected Area floor marking

- Self-adhesive
- 75mm wide, 33m long roll
- PVC laminated with clear PP for durability and washability